

**Continental**



**HTC**



CONTINENTAL  
MEDIUM TRUCK

# HTC

## SUPER SINGLE ON/OFF HIGHWAY SERVICE (HEAVY TRAILER CONSTRUCTION)

Aggressive multi-service all-position tread pattern provides excellent traction in on/off road service.

Cut and tear resistant tread compound for on/off highway service.

Thick undertread resists casing penetration and damage for multiple retreads.



### Applications:

Super single all-position fitment for on/off highway service.

### TIRE SPECIFICATIONS

Highway - 65 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION SINGLE		MAX LOAD@INFLATION DUAL	
													lbs	psi	lbs	psi
385/65R22.5*	L	21/32	0211218	05753160000	11.75* <sup>Δ</sup>	42.4 (1077)	15.3 (389)	16.1 (409)	19.5 (495)	NA	488 (303)	162 (74)	9920 (4500)	130 (900)	NA	NA
425/65R22.5*	L	21/32	0210986	05753260000	13.00	44.5 (1130)	16.6 (422)	18.0 (457)	20.6 (523)	NA	465 (289)	192 (87)	11,400 (5150)	120 (830)	NA	NA
445/65R22.5*	L	21/32	0210994	05753270000	14.00	45.5 (1156)	17.5 (445)	18.9 (480)	21.0 (533)	NA	455 (283)	208 (94)	12,300 (5600)	120 (830)	NA	NA

Note: Minimum Dual Spacing calculated without chains.  
These specifications subject to change without notice.

\*ECE Certified  
<sup>Δ</sup> Alternate approved rim 12.25