

Continental



HTR



CONTINENTAL
MEDIUM TRUCK

HTR

ALL-POSITION TRAILER (HEAVY TRAILER REGIONAL)

Multiple-rib tread design features excellent wet traction and lateral stability.

High ply ratings provide durability for long casing life and multiple retreads.

See through grooves aid in water evacuation providing excellent wet traction.



Applications:

Long haul and over the highway
all-position use.

TIRE SPECIFICATIONS Highway - 65 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE lbs (KG)	psi (KPa)	DUAL lbs (KG)	psi (KPa)
TUBELESS TIRES ON 15 DEGREE DROP CENTER RIMS																
215/75R17.5*	H	15/32	0210846	04544200000	6.00	30.2 (767)	8.3 (211)	8.7 (221)	14.1 (358)	9.3 (236)	685 (426)	58 (26)	4805 (2180)	125 (860)	4540 (2060)	125 (860)
235/75R17.5*	H	16/32	0210842	04544280000	6.75	31.4 (798)	9.2 (234)	9.7 (246)	14.7 (373)	10.3 (262)	660 (410)	67 (30)	6005 (2725)	125 (860)	5675 (2575)	125 (860)
385/65R22.5*	L	19/32	0211228	05723310000	11.75 [▲]	42.2 (1072)	15.3 (389)	16.1 (409)	19.5 (495)	NA	491 (305)	158 (72)	9920 (4500)	130 (900)	NA	NA
425/65R22.5* (**)	L	18/32	0206067	05723160000	13.00	44.3 (1125)	16.6 (422)	18.0 (457)	20.5 (521)	NA	468 (291)	188 (85)	11,400 (5150)	120 (830)	NA	NA
445/65R22.5* (**)	L	18/32	0205498	05723210000	14.00	45.3 (1151)	17.5 (445)	18.9 (480)	20.9 (531)	NA	457 (284)	203 (92)	12,300 (5600)	120 (830)	NA	NA
TUBETYPE TIRES ON TYPE I, II, III RIMS																
8.25R15*+ [#]	J	17/32	0206138	04140660000	6.50	32.9 (836)	9.2 (234)	9.5 (241)	15.1 (384)	10.6 (269)	629 (391)	61 (28)	5840 (2650)	120 (830)	5675 (2575)	120 (830)
365/80R20*	L	18/32	0205494	05721730000	10.00	43.0 (1092)	13.7 (348)	15.0 (381)	19.7 (501)	NA	480 (298)	168 (76)	9920 (4500)	120 (830)	NA	NA

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.
([#])8.25R15 can be used with max. inflation 140 psi with high capacity rims
[▲]Alternate approved rim 12.25

*ECE Certified
(**)Tread pattern may vary
(†)Max speed 55mph