

Continental



LSR



CONTINENTAL
MEDIUM TRUCK

LSR

GENERAL PURPOSE ALL-POSITION SERVICE (LIGHT STEER REGIONAL)

Economical, multi-rib radials designed for even wear, wet traction and high mileage.

Multi-service tread compound for local and long haul service.

Solid shoulder design reduces noise and provides even tread wear.



Applications:

General rib designs for all-position service.
Local delivery, school buses and trailers.

TIRE SPECIFICATIONS

Highway - 65 mph at loads indicated unless otherwise stated.

TIRE SIZE	LOAD RANGE	TREAD DEPTH	PRODUCT CODE	SAP ARTICLE NUMBER	RIM WIDTH IN	OVERALL INFLATED DIAMETER IN (mm)	OVERALL INFLATED WIDTH IN (mm)	LOADED SECTION WIDTH IN (mm)	STATIC LOADED RADIUS IN (mm)	MINIMUM DUAL SPACING IN (mm)	REVS PER MILE (KM)	TIRE WEIGHT LB (KG)	MAX LOAD@INFLATION			
													SINGLE		DUAL	
												lbs	psi	lbs	psi	
8R17.5*	F	15/32	0125989	04714010000	5.25	30.9 (785)	7.9 (201)	8.1 (206)	14.5 (368)	9.1 (231)	671 (417)	48 (22)	2835 (1285)	85 (590)	2755 (1250)	85 (590)
8.5R17.5*	F	15/32	0125911	04714020000	6.00	31.6 (803)	8.5 (216)	8.7 (221)	14.7 (373)	9.5 (241)	656 (408)	51 (23)	3195 (1450)	90 (620)	3085 (1400)	90 (620)
10R17.5*	H	17/32	0125994	04714040000	7.50	33.8 (859)	10.0 (254)	10.3 (262)	15.7 (399)	11.4 (290)	613 (381)	69 (31)	4675 (2120)	115 (790)	4410 (2000)	115 (790)

Note: Minimum Dual Spacing calculated without chains.
These specifications subject to change without notice.

*ECE Certified